



# TUALAJ 4100-MINI GNSS ANTI-JAM CRPA SYSTEM

## GENERAL DESCRIPTION

TUALCOM Anti-Jam GNSS CRPA System supports critical missions by providing jam free GNSS signals.

The system eliminates interference by applying novel beamforming techniques. With a 4-array CRPA antenna, the system can assure the normal operation of GNSS receiver in presence of multiple jamming sources.

TUALCOM Anti-Jam GNSS CRPA System can be employed using various configurations and operates with civil and military GPS receivers for the land, sea, air platforms (including unmanned aerial systems) and fixed installations. The product has an embedded GNSS receiver. Wide bandwidth of the system also enables the SBAS signals to GNSS receiver.

The system can be provided with various types of antennas. Physical solutions for further suppression performance such as elevation masking can also be provided as antenna option.

## BENEFITS

- Immediate availability for urgent operational needs
- Simple assembly means easy to install or retrofit
- Compatible with all types of external GPS receivers and vehicle navigation systems
- Minimal integration training required
- Light Weight
- Ultra Compact Size
- Superior Suppression Performance
- Embedded GNSS Receiver Option
- Integrates easily into new or legacy platforms
- Assured PNT

## APPLICATION AREAS

- Fixed Winged Aircraft
- Rotary Wing Aircraft
- Guided Munitions
- Unmanned Autonomous Systems
- Armored Vehicles
- Naval Platforms, Coast Guard Platforms
- Maritime Cybersecurity
- Advanced Transportation Systems
- Military Communications
- Armored Trucks, Critical Asset Tracking

# TUALAJ 4100-MINI

## GNSS ANTI-JAM CRPA SYSTEM



### Weight (g)

**180**

### Dimensions (cm)

**7.2 x 7.2 x 2.275**

### Power Consumption (w)

**<6**

### Antenna Array

**4**

### Simultaneous Active Bands

**1**

### Simultaneous Independent Nulling

**3**

### Nominal Wideband Suppression

**>40 dB**

### Data Interfaces

**Ethernet, Serial**

### Bandwidth

**Up To 30 Mhz** (Depends to selected band option)

### Connectors

**1 x SMA Female, Micro-D 9-pin Socket**

### Operating Voltage

**5 Vdc**

### Operating Temp

**-40 °C To +85 °C**

### Internal GNSS Receiver

**GPS L1 / Galileo E1 / SBAS**

### Internal GNSS Tracking Sensitivity

**-164 dBm**

### RTCM Support





**Yes**

### Environmental Tests

**MIL-STD-810G**

### EMI / EMC

**MIL-STD-461F**

TUALAJ 4100 MINI	TUALAJ 4100	TUALAJ 4200	TUALAJ 4300
			
<b>GPS L1</b>	<b>GPS L1</b>	<b>GPS L1 GPS L2/GLONASS L1</b>	<b>GPS L1 GPS L2, GLONASS L1</b>
<b>All TUALAJ Product Family Supports Galileo and BeiDou</b>			

## TUALCOM ELEKTRONİK A.Ş.

T: +90 312 485 22 85

e-mail: [info@tualcom.com.tr](mailto:info@tualcom.com.tr)

© 2020 TUALCOM; The information contained herein is subject to change without notice. TUALCOM A.Ş. cannot be held responsible for this and no liability is accepted for any errors or omissions.

